

# STILEX

VINYL FLOORING

WOOD STRIPS

WOOD PLANKS

MARBLE TILES

SPARKLE TILES

CARPET TILES

PARQUET PLANKS

For Lower Traffic Areas  
LATEST COLLECTION RANGE  
2019-2020

Step in Style Step on STILEX

## 1.2mm Vinyl Planks

Size: 6"x36" Packing: 40pcs/60sqft per box.



126



127



128



129



131



## 1.2mm Vinyl Planks

Size: 6"x36" Packing: 40pcs/60sqft per box.



121



122



123



124



130

## 1.5mm Vinyl Planks

Size: 6"x36" Packing: 30pcs/45sqft per box.



6000



8008



8105



8174



3302



2976



## 1.5mm Vinyl Planks

Size: 6"x36" Packing: 30pcs/45sqft per box.



2705



3901



2704



2711



1779



6601



## 1.5mm Vinyl Planks

Size: 6"x36" Packing: 30pcs/45sqft per box.



1001A



1001C



2023



1776



6003



2978



## 2.0mm Vinyl Planks

Size: 6"x36" Packing: 24pcs/36sqft per box.



5267



3664



5188



3364

## 2.0mm Vinyl Planks

Size: 6"x36" Packing: 24pcs/36sqft per box.



1477



5189



2030



2186



## 2.0mm Vinyl Planks

Size: 6"x36" Packing: 24pcs/36sqft per box.



3508



3505



2977



2979

# STILEX

VINYL FLOORING

## Description :

STILEX vinyl floorings are available in a variety of design, thickness and textures for different applications for both residential and commercial use. These flooring tiles, strips and planks are non asbestos flexible vinyl floorings brought to you with a combination of elegance, warmth, charm and richness of natural products like wood and marble. The wood planks and carpet tiles are available with an exceptional heavy duty wear layer of 0.3 mm which gives the product an excellent abrasion resistance. Stilex tiles and planks also have a matt finish UV coating to protect colour fading and also provide a dust repellent surface for easy maintenance.

## Application :

STILEX products are ideally suited for installation in any residential, commercial and public area such as offices, restaurants, shopping areas, schools, lifts, etc where a low maintenance, rich looking flooring solution is required. It is strongly recommended that 1.2/1.5/2.0 mm products are not used in high commercial areas where very heavy traffic load is expected.

## Installation :

STILEX vinyl products are ideal for laying on any smooth, dry, hard and even surface including timber and concrete. However, care must be taken to ensure that the sub floor is completely free from any moisture, oil, grease, dirt, etc.

Suitable quality adhesive such as Fevicol 998 / 505 / Dunlop S 758 or equivalent should be used. Water based adhesives such as VC 31 can also be used. Sufficient drying time must be given before walking on the newly installed floor.

The job of installation must only be carried out by a trained and experienced floor contractor.

## Maintenance :

It is important to place an entrance mat to trap outside dust from entering. Any food spills must be immediately cleaned up with a non abrasive general cleaner. Regular cleaning is advised with a dry vacuum cleaner or mopping. When mopping the floor with water, care must be taken to ensure that water does not seep in through the joints. Since these flooring products are already coated with a UV protective layer dust retention will be at the minimal. Waxing is not required. Always ensure that all furniture legs are fitted with floor protectors.

Imported by :

**Raj Agencies**

[stilexfloors@gmail.com](mailto:stilexfloors@gmail.com)

[www.stilex.in](http://www.stilex.in)

**NOT:** This card depicts our standard shades which may vary slightly from batch to batch.