

**STILEX**

**IMPACT**

®

**A BETTER FLOOR**

**TRANQUIL**®

**SPC FLOORING**



**14F DROP CLICK SYSTEM**



RESPONSIVE 

**IMPACT**  
A BETTER FLOOR

A BETTER  
FLOOR

TILE SIZE: 12" x 24" x 5.0 mm

## TRANQUIL<sup>®</sup>

SPC FLOORING

SIZE: 12" x 24" | 300 x 600 mm

THICKNESS: 5.0 MM

WEAR LAYER: 12 MIL | 0.30 MM

PIECES: 12 PER BOX

COVERAGE: 23.25 SQ FT / BOX | 2.16 M<sup>2</sup> / BOX

INTERLOCK: I4F DROP CLICK SYSTEM

**TRANQUIL**  
SPC FLOORING: I4F CLICK SYSTEM

SPC FLOORING FOR HEAVY COMMERCIAL USE    PUR Polyurethane Reinforcement    |    Product Standard TRANQUIL ASTM F3261-17

CERTIFICATION & CLASSIFICATION	STANDARD	TRANQUIL®
TYPE OF FLOOR COVERING	ISO 10582	SPC
CE CERTIFICATION	EN 14041	Yes
CLASSIFICATION	EN ISO 10874	Heavy Traffic : Class 33
TECHNICAL CHARACTERISTICS	STANDARDS	TRANQUIL®
TOTAL THICKNESS	EN ISO 2436 (EN 428)	5.0 MM
WEAR LAYER THICKNESS	EN ISO 24340 (EN 429)	0.50 MM   20 MIL
SURFACE TREATMENT	UV TREATED	PUR
TOTAL WEIGHT	EN ISO 23997 (EN 430)	8.5 kg/m <sup>2</sup>   1.74 lbs / sq.ft
WEAR LAYER BINDER CONTENT	ISO 10582	TYPE I
FORM OF DELIVERY	EN ISO 24342 ( EN 427) Planks box	12" X 24" = 23.25 sq.ft   12 Pieces per box 300 x 600 mm = 12.16 m <sup>2</sup>   12 Pieces per box
TECHNICAL PERFORMANCES	STANDARDS	TRANQUIL®
DIMENSIONAL STABILITY	EN ISO 23999 ( EN 434)	≤ 0.10%
REACTION TO FIRE	EN 13501 - 1	Bfl- S1
RESIDUAL INDENTATION	EN ISO 24343-1 (EN 433)	PASS
FURNITURE LEG	EN 424	No damage
CASTOR CHAIR	EN ISO 4918 (EN 425)	No damage
CURL RESULTANT TO HEAT	EN ISO 23999 (434)	≤ 2mm
IMPACT SOUND REDUCTION	EN ISO 140-8 EN ISO 717/2	L <sub>nw</sub> = 18 dB
LIGHT FASTNESS	EN ISO 105 - B02	> Grade 6
RESISTANCE TO CHEMICALS	EN ISO 26987 (EN423)	Good Resistance
SLIP RESISTANCE	DIN51130   EN 13893	R9   PASS
ELECTRICAL PROPERTIES	EN 1815   EN1081	< 2 kV On Concrete   R1 > 1010 Ω




**ISO 9001**  
**ISO 14001**  
**ISO 18001**









**TRANQUIL**  
SPC FLOORING: I4F CLICK SYSTEM



**FEATURES & BENEFITS**

 Superior Scratch & Stain Resistant	 No Bugs & Termites	 No Adhesive Required	 100% Waterproof	 Easy Clean
 Natural Looking Design	 Zero Maintenance	 Superb Dimensional Stability	 Heavy Foot Traffic	 Excellent Sound Insulation

**APPLICATIONS**

 Corporate Offices	 Residential
 Retail	 Hospitality



**BELLAGIO BEIGE**

**IMP-TRQ-03**

**RESPONSIVE** 

**IMPACT**<sup>®</sup>  
A BETTER FLOOR



# BELLAGIO BEIGE

IMP-TRQ-03





---

# BELLAGIO BEIGE

IMP-TRQ-03

## 8 UNIQUE PATTERN VARIATIONS



A



B



C



D



E



F



G



H



**SMOKE GRANITE**

**IMP-TRQ-07**

**RESPONSIVE** 

**IMPACT**<sup>®</sup>  
A BETTER FLOOR



**SMOKE GRANITE**

**IMP-TRQ-07**






---


# **SMOKE GRANITE**

**IMP-TRQ-07**


## **8 UNIQUE PATTERN VARIATIONS**



**A**



**B**




**C**




**D**




**E**



**F**



**G**



**H**



---

**AMERICAN BASALT**

**IMP-TRQ-09**

**RESPONSIVE** 

**IMPACT**  
A BETTER FLOOR



---

# AMERICAN BASALT

## IMP-TRQ-09





---

# AMERICAN BASALT

IMP-TRQ-09

## 8 UNIQUE PATTERN VARIATIONS



A



B



C



D



E



F



G



H